Clor/035 Incoming



Sunnyside Cogeneration Associates

P.O. Box 10, East Carbon, Utah 84520 • (435) 888-4476 • Fax (435) 888-2538

January 29, 2013

Daron Haddock Utah Division of Oil, Gas & Mining 1594 W. North Temple, Suite 1210 Salt Lake City, Utah 84116

RECEIVED
JAN 3 1 2013

RE: 4th Quarter 2012 Inspection Report Sunnyside Refuse Pile C/007/035

DIV. OF OIL, GAS & MINING

Dear Daron:

Please find enclosed a copy of the fourth Quarter 2012 Inspection Report for Sunnyside Cogeneration Associates' impoundments, refuse pile and excess spoil areas.

Should you have any questions, please contact Rusty Netz or myself at $(435)\,888-4476$.

Thank You,

Richard Carter

Agent For

Sunnyside Cogeneration Associates

c.c. Rusty Netz Plant File

GENERAL INFORMATION

Railcut Sediment Pond

Report Date

January 14, 2013

Permit Number

C/007/035

Mine Name

Sunnyside Refuse and Slurry

Company Name

Sunnyside Cogeneration Associates

IMPOUNDMENT IDENTIFICATION

Impoundment Name

RailCut Sediment Pond

Impoundment Number

007

UPDES Permit Number

UT024759

MSHA ID Number

N/A

IMPOUNDMENT INSPECTION

Inspection Date

December 17, 2012

Inspected by

Rusty Netz

Reason for Inspection

Fourth Quarter Inspection 2012

1. Describe any appearance of any instability, structural weakness, or any other hazardous condition.

None

a. Sediment storage capacity, including elevation of 60% and 100% sediment storage volumes, and estimated average elevation of existing sediment.

Total Pond Volume = 4.8 Acre-feet

Pond bottom elevation = 6206.0

100% Sediment Storage Volume = 0.34 acre-feet at Elevation 6209

60% sediment Storage Volume = 0.2 acre feet at Elevation = 6207.7

Existing Sediment Elevation = 6207.2 +/-

b. Principle and emergency spillway elevations.

Primary Dewatering Pipe = 6209.07

Emergency Spillway Elevation = 6212.34

2. Field Information

Provide current water elevation, whether pond is discharging, type and number of samples taken, monitoring/instrumentation information, inlet/outlet conditions, or other related activities associated with the pond including but not limited to sediment cleanout, pond decanting, embankment erosion/repairs, monitoring information, vegetation on outslopes of embankments, etc.

Pond had some snow cover. No samples were taken Pond did not require decanting Sediment levels were good

Embankment conditions were good. Vegetation on outslopes was adequate.

Rail Cut Sediment Pond

3. Field Evaluation.

Describe any changes in the geometry of the impounding structure, average and maximum depths and elevation of impounded water, estimated sediment or slurry volume and remaining storage capacity, estimated volume of water impounded, and any other aspect of the impounding structure affecting its stability or function which has occurred during the reporting period

No recent changes in the geometry of the structure have been observed

No water was impounded

No other aspects of the impounding structure were observed that could affect its stability or functionality.

OUALIFICATION STATEMENT:

I hereby certify that; I am experienced in the construction of impoundments; I am qualified and authorized under the direction of a Registered Professional Engineer to inspect the condition and appearance of impoundments in accordance with the certified and approved designs for this structure; that the impoundment has been maintained in accordance with approved designs and meets or exceeds the minimum design requirements under all applicable federal, state and local regulations; and that inspections are made by myself and include any appearances of instability, structural weakness or other hazardous condition of the structure affecting stability.

Signature:

Date:

CERTIFIED REPORT

IMPOUNDMENT EVALUATION

If you answer NO to these questions, please explain under comments

1. Is impoundment designed and constructed in accordance with the approved plan?

YES

2. Is impoundment free of instability, structural weakness, or any other hazardous conditions?

3. Has the impoundment met all applicable performance standards and effluent limitations

3. Has the impoundment met an applicable performance standards and efficient immations

from the previous date of inspection?

YES

COMMENTS/ OTHER INFORMATION

None

CERTIFICATION STATEMENT:

I hereby certify that: I am experienced in the construction of impoundments; I am qualified and authorized in the State of Utah to inspect and certify the condition and appearance of impoundments in accordance with the certified and approved designs for this structure; that the impoundment has been maintained in accordance with approved designs and meets or exceeds the minimum design requirements under all applicable federal, state and local regulations; and that inspections and inspection reports are made by myself or under my direction and include any appearances of instability, structural weakness or other hazardous conditions of the structure affecting stability in accordance with the Utah R645 Coal Mining Rules.

By: S. Scott Carlson, PE, Twin Peaks, P.C.

P.E. Number & State: 187727 UTAH

Old Coarse Refuse Road Sediment Pond

GENERAL INFORMATION

Report Date <u>January 14, 2013</u>

Permit Number <u>C/007/035</u>

Mine Name Sunnyside Refuse and Slurry

Company Name Sunnyside Cogeneration Associates

IMPOUNDMENT IDENTIFICATION

Impoundment Name Old Coarse Refuse Road Sediment Pond

Impoundment Number 008

UPDES Permit Number <u>UT024759</u>

MSHA ID Number N/A

IMPOUNDMENT INSPECTION

Inspection Date <u>December 17, 2012</u>

Inspected by Rusty Netz

Reason for Inspection Fourth Quarter Inspection 2012

1. Describe any appearance of any instability, structural weakness, or any other hazardous condition.

None

a. Sediment storage capacity, including elevation of 60% and 100% sediment storage volumes, and estimated average elevation of existing sediment.

Total Pond Volume = 0.9 Acre-feet Pond bottom elevation = 6394.0

100% Sediment Storage Volume = 0.08 acre-feet at Elevation 6395.1

60% sediment Storage Volume = 0.05 acre feet at Elevation = 6394.75

Existing Sediment Elevation = 6394.4 +/-

b. Principle and emergency spillway elevations.

Primary Dewatering Pipe = 6395.75

Emergency Spillway Elevation = 6399.4

2. Field Information

Provide current water elevation, whether pond is discharging, type and number of samples taken, monitoring/instrumentation information, inlet/outlet conditions, or other related activities associated with the pond including but not limited to sediment cleanout, pond decanting, embankment erosion/repairs, monitoring information, vegetation on outslopes of embankments, etc.

Pond had some snow cover. No samples were taken Pond did not require decanting. Sediment level was good.

Embankment conditions were good. Vegetation on outslopes was adequate.

Old Coarse Refuse Road Sediment Pond

3. Field Evaluation.

Describe any changes in the geometry of the impounding structure, average and maximum depths and elevation of impounded water, estimated sediment or slurry volume and remaining storage capacity, estimated volume of water impounded, and any other aspect of the impounding structure affecting its stability or function which has occurred during the reporting period

No recent changes in the geometry of the structure have been observed

No water was impounded

Sediment level was good.

No other aspects of the impounding structure were observed that could affect its stability or functionality.

OUALIFICATION STATEMENT:

I hereby certify that; I am experienced in the construction of impoundments; I am qualified and authorized under the direction of a Registered Professional Engineer to inspect the condition and appearance of impoundments in accordance with the certified and approved designs for this structure; that the impoundment has been maintained in accordance with approved designs and meets or exceeds the minimum design requirements under all applicable federal, state and local regulations; and that inspections are made by myself and include any appearances of instability, structural weakness or other hazardous condition of the structure affecting

Signature:

Date: 1/29/13

CERTIFIED REPORT IMPOUNDMENT EVALUATION

If you answer NO to these questions, please explain under comments

1. Is impoundment designed and constructed in accordance with the approved plan?

2. Is impoundment free of instability, structural weakness, or any other hazardous conditions?

3. Has the impoundment met all applicable performance standards and effluent limitations

from the previous date of inspection?

COMMENTS/ OTHER INFORMATION

None

CERTIFICATION STATEMENT:

I hereby certify that: I am experienced in the construction of impoundments; I am qualified and authorized in the State of Utah to inspect and certify the condition and appearance of impoundments in accordance with the certified and approved designs for this structure; that the impoundment has been maintained in accordance with approved designs and meets or exceeds the minimum design requirements under all applicable federal, state and local regulations; and that inspections and inspection reports are made by myself or under my direction and include any appearances of instability, structural weakness or other hazardous conditions of the structure affecting stability in accordance with the Utah R645 Coal Mining Rules.

S. Scott Carlson, PE, Twin Peaks, P.C. By:

P.E. Number & State: 187727 UTAH

Pasture Sediment Pond

GENERAL INFORMATION

Report Date <u>January 14, 2013</u>

Permit Number <u>C/007/035</u>

Mine Name Sunnyside Refuse and Slurry

Company Name <u>Sunnyside Cogeneration Associates</u>

IMPOUNDMENT IDENTIFICATION

Impoundment Name Pasture Sediment Pond

Impoundment Number 009

UPDES Permit Number <u>UT024759</u>

MSHA ID Number <u>N/A</u>

IMPOUNDMENT INSPECTION

Inspection Date <u>December 17, 2012</u>

Inspected by Rusty Netz

Reason for Inspection Fourth Quarter Inspection 2012

1. Describe any appearance of any instability, structural weakness, or any other hazardous condition.

None

a. Sediment storage capacity, including elevation of 60% and 100% sediment storage volumes, and estimated average elevation of existing sediment.

Total Pond Volume = 3.2 Acre-feet
Pond bottom elevation = 6484.5
100% Sediment Storage Volume = 0.42 acre-feet at Elevation 6486.2
60% sediment Storage Volume = 0.25 acre feet at Elevation = 6485.5
Existing Sediment Elevation = 6485.1 +/-

b. Principle and emergency spillway elevations.

Primary Dewatering Pipe = 6486.6 Emergency Spillway Elevation = 6490.6

2. Field Information

Provide current water elevation, whether pond is discharging, type and number of samples taken, monitoring/instrumentation information, inlet/outlet conditions, or other related activities associated with the pond including but not limited to sediment cleanout, pond decanting, embankment erosion/repairs, monitoring information, vegetation on outslopes of embankments, etc.

Pond had some snow cover. No samples were taken Pond did not require decanting. Sediment level was good

Embankment conditions were good. Vegetation on outslopes was adequate.

Pasture Sediment Pond

3. Field Evaluation.

Describe any changes in the geometry of the impounding structure, average and maximum depths and elevation of impounded water, estimated sediment or slurry volume and remaining storage capacity, estimated volume of water impounded, and any other aspect of the impounding structure affecting its stability or function which has occurred during the reporting period

No recent changes in the geometry of the structure were observed.

No water was impounded

Sediment level was good.

No other aspects of the impounding structure were observed that could affect its stability or functionality.

QUALIFICATION STATEMENT:

I hereby certify that; I am experienced in the construction of impoundments; I am qualified and authorized under the direction of a Registered Professional Engineer to inspect the condition and appearance of impoundments in accordance with the certified and approved designs for this structure; that the impoundment has been maintained in accordance with approved designs and meets or exceeds the minimum design requirements under all applicable federal, state and local regulations; and that inspections are made by myself and include any appearances of instability, structural weakness or other hazardous condition of the structure affecting stability.

CERTIFIED REPORT IMPOUNDMENT EVALUATION

If you answer NO to these questions, please explain under comments

1. Is impoundment designed and constructed in accordance with the approved plan?

2. Is impoundment free of instability, structural weakness, or any other hazardous conditions?

3. Has the impoundment met all applicable performance standards and effluent limitations

from the previous date of inspection?

YES

COMMENTS/ OTHER INFORMATION

None

CERTIFICATION STATEMENT:

I hereby certify that: I am experienced in the construction of impoundments; I am qualified and authorized in the State of Utah to inspect and certify the condition and appearance of impoundments in accordance with the certified and approved designs for this structure; that the impoundment has been maintained in accordance with approved designs and meets or exceeds the minimum design requirements under all applicable federal, state and local regulations; and that inspections and inspection reports are made by myself or under my direction and include any appearances of instability, structural weakness or other hazardous conditions of the structure affecting stability in accordance with the Utah R645 Coal Mining Rules.

S. Scott Carlson, PE, Twin Peaks, P.C.

P.E. Number & State: 187727 UTAH

Affix Signature, Stamp and Date

Page 6 of 18

Coarse Refuse Toe Sediment Pond

GENERAL INFORMATION

Report Date

January 14, 2013

Permit Number

C/007/035

Mine Name

Sunnyside Refuse and Slurry

Company Name

Sunnyside Cogeneration Associates

IMPOUNDMENT IDENTIFICATION

Impoundment Name

New Coarse Refuse Toe Sediment Pond

Impoundment Number

UPDES Permit Number

UT0<u>24759</u>

MSHA ID Number

N/A

012

IMPOUNDMENT INSPECTION

Inspection Date

December 17, 2012

Inspected by

Rusty Netz

Reason for Inspection

Fourth Quarter Inspection 2012

1. Describe any appearance of any instability, structural weakness, or any other hazardous condition.

None

a. Sediment storage capacity, including elevation of 60% and 100% sediment storage volumes, and estimated average elevation of existing sediment.

Total Pond Volume = 1.6 Acre-feet

Pond bottom elevation = 6176.0

100% Sediment Storage Volume = 0.07 acre-feet at Elevation 6177.8

60% sediment Storage Volume = 0.03 acre feet at Elevation = 6177.0

Existing Sediment Elevation = 6176.6 + -

b. Principle and emergency spillway elevations.

Primary Dewatering Pipe = 6178.2

Emergency Spillway Elevation = 6183.63

2. Field Information

Provide current water elevation, whether pond is discharging, type and number of samples taken, monitoring/instrumentation information, inlet/outlet conditions, or other related activities associated with the pond including but not limited to sediment cleanout, pond decanting, embankment erosion/repairs, monitoring information, vegetation on outslopes of embankments, etc.

Pond had some snow cover. No samples were taken Pond did not require decanting Sediment level was good

Embankment conditions were good. Vegetation on outslopes was adequate.

Coarse Refuse Toe Sediment Pond

3. Field Evaluation.

Describe any changes in the geometry of the impounding structure, average and maximum depths and elevation of impounded water, estimated sediment or slurry volume and remaining storage capacity, estimated volume of water impounded, and any other aspect of the impounding structure affecting its stability or function which has occurred during the reporting period

No recent changes in the geometry of the structure have been observed

No water was impounded

Sediment level was good.

No other aspects of the impounding structure were observed that could affect its stability or functionality.

QUALIFICATION STATEMENT:

I hereby certify that; I am experienced in the construction of impoundments; I am qualified and authorized under the direction of a Registered Professional Engineer to inspect the condition and appearance of impoundments in accordance with the certified and approved designs for this structure; that the impoundment has been maintained in accordance with approved designs and meets or exceeds the minimum design requirements under all applicable federal, state and local regulations; and that inspections are made by myself and include any appearances of instability, structural weakness or other hazardous condition of the structure affecting stability.

Signature:

Date:

CERTIFIED REPORT

IMPOUNDMENT EVALUATION

If you answer NO to these questions, please explain under comments

1. Is impoundment designed and constructed in accordance with the approved plan?

YES

2. Is impoundment free of instability, structural weakness, or any other hazardous conditions?

3. Has the impoundment met all applicable performance standards and effluent limitations from the previous date of inspection?

YES

COMMENTS/ OTHER INFORMATION

None

CERTIFICATION STATEMENT:

I hereby certify that: I am experienced in the construction of impoundments; I am qualified and authorized in the State of Utah to inspect and certify the condition and appearance of impoundments in accordance with the certified and approved designs for this structure; that the impoundment has been maintained in accordance with approved designs and meets or exceeds the minimum design requirements under all applicable federal, state and local regulations; and that inspections and inspection reports are made by myself or under my direction and include any appearances of instability, structural weakness or other handlous conditions of the structure affecting stability in accordance with the Utah R645 Coal Mining Rules.

By: S. Scott Carlson, PE, Twin Peaks, P.C.

P.E. Number & State: 187727 UTAH

GENERAL INFORMATION

Coal Pile Sediment Pond

Report Date

January 14, 2013

Permit Number

C/007/035

Mine Name

Sunnyside Refuse and Slurry

Company Name

Sunnyside Cogeneration Associates

IMPOUNDMENT IDENTIFICATION

Impoundment Name

Coal Pile Sediment Pond

Impoundment Number

014

UPDES Permit Number

UT024759

MSHA ID Number

N/A

IMPOUNDMENT INSPECTION

Inspection Date

December 17, 2012

Inspected by

Rusty Netz

Reason for Inspection

Fourth Quarter Inspection 2012

1. Describe any appearance of any instability, structural weakness, or any other hazardous condition.

None

a. Sediment storage capacity, including elevation of 60% and 100% sediment storage volumes, and estimated average elevation of existing sediment.

Total Pond Volume = 1.5 Acre-feet

Pond bottom elevation = 6473.0

100% Sediment Storage Volume = 0.5 acre-feet at Elevation 6476.0

60% sediment Storage Volume = 0.3 acre feet at Elevation = 6474.7

Existing Sediment Elevation = 6474 +/-

b. Principle and emergency spillway elevations.

Primary Dewatering Pipe = 6476.0

Secondary Dewatering Orifice = 6477.2

Primary Spillway Elevation = 6477.9

Emergency Spillway Elevation = 6479.0

2. Field Information

Provide current water elevation, whether pond is discharging, type and number of samples taken, monitoring/instrumentation information, inlet/outlet conditions, or other related activities associated with the pond including but not limited to sediment cleanout, pond decanting, embankment erosion/repairs, monitoring information, vegetation on outslopes of embankments, etc.

Pond had some snow cover. No samples were taken Pond did not require decanting. Sediment level was good.

Embankment conditions were good. Vegetation on outslopes was adequate.

Coal Pile Sediment Pond

3. Field Evaluation.

Describe any changes in the geometry of the impounding structure, average and maximum depths and elevation of impounded water, estimated sediment or slurry volume and remaining storage capacity, estimated volume of water impounded, and any other aspect of the impounding structure affecting its stability or function which has occurred during the reporting period

No recent changes in the geometry of the structure have been observed

No water was impounded

Sediment level was good.

No other aspects of the impounding structure were observed that could affect its stability or functionality.

OUALIFICATION STATEMENT:

I hereby certify that; I am experienced in the construction of impoundments; I am qualified and authorized under the direction of a Registered Professional Engineer to inspect the condition and appearance of impoundments in accordance with the certified and approved designs for this structure; that the impoundment has been maintained in accordance with approved designs and meets or exceeds the minimum design requirements under all applicable federal, state and local regulations; and that inspections are made by myself and include any appearances of instability, structural weakness or other hazardous condition of the structure affecting stability.

Signature:

Date:

CERTIFIED REPORT

IMPOUNDMENT EVALUATION

If you answer NO to these questions, please explain under comments

1. Is impoundment designed and constructed in accordance with the approved plan?

2. Is impoundment free of instability, structural weakness, or any other hazardous conditions?

3. Has the impoundment met all applicable performance standards and effluent limitations

from the previous date of inspection?

YES

COMMENTS/OTHER INFORMATION

None

CERTIFICATION STATEMENT:

I hereby certify that: I am experienced in the construction of impoundments; I am qualified and authorized in the State of Utah to inspect and certify the condition and appearance of impoundments in accordance with the certified and approved designs for this structure; that the impoundment has been maintained in accordance with approved designs and meets or exceeds the minimum design requirements under all applicable federal, state and local regulations; and that inspections and inspection reports are made by myself or under my direction and include any appearances of instability, structural weakness or other hazardous conditions of the structure affecting stability in accordance with the Utah R645 Coal Mining Rules.

S. Scott Carlson, PE, Twin Peaks, P.C. By:

P.E. Number & State: 187727 UTAH

Borrow Area Sediment Pond

GENERAL INFORMATION

Report Date

January 14, 2013

Permit Number

C/007/035

Mine Name

Sunnyside Refuse and Slurry

Company Name

Sunnyside Cogeneration Associates

IMPOUNDMENT IDENTIFICATION

Impoundment Name

Borrow Area Sediment Pond

Impoundment Number

016

UPDES Permit Number

UT024759

MSHA ID Number

N/A

IMPOUNDMENT INSPECTION

Inspection Date

December 17, 2012

Inspected by

Rusty Netz

Reason for Inspection

Fourth Quarter Inspection 2012

1. Describe any appearance of any instability, structural weakness, or any other hazardous condition.

None

a. Sediment storage capacity, including elevation of 60% and 100% sediment storage volumes, and estimated average elevation of existing sediment.

Total Pond Volume = 8.3 Acre-feet

Pond bottom elevation = 6510.0

100% Sediment Storage Volume = 2.3 acre-feet at Elevation 6514.3

60% sediment Storage Volume = 1.4 acre feet at Elevation = 6513.3

Existing Sediment Elevation = 6511 +/-

b. Principle and emergency spillway elevations.

Primary Dewatering Pipe = 6514.3

Emergency Spillway Elevation = 6517.03

2. Field Information

Provide current water elevation, whether pond is discharging, type and number of samples taken, monitoring/instrumentation information, inlet/outlet conditions, or other related activities associated with the pond including but not limited to sediment cleanout, pond decanting, embankment erosion/repairs, monitoring information, vegetation on outslopes of embankments, etc.

Pond had some snow cover. No samples were taken

Sediment level was good. Pond did not require decanting.

Embankment conditions were good. Vegetation on outslopes was adequate.

Borrow Area Sediment Pond

3. Field Evaluation.

Describe any changes in the geometry of the impounding structure, average and maximum depths and elevation of impounded water, estimated sediment or slurry volume and remaining storage capacity, estimated volume of water impounded, and any other aspect of the impounding structure affecting its stability or function which has occurred during the reporting period

No recent changes in the geometry of the structure have been observed

No water was impounded

Sediment level was good.

No other aspects of the impounding structure were observed that could affect its stability or functionality.

QUALIFICATION STATEMENT:

I hereby certify that; I am experienced in the construction of impoundments; I am qualified and authorized under the direction of a Registered Professional Engineer to inspect the condition and appearance of impoundments in accordance with the certified and approved designs for this structure; that the impoundment has been maintained in accordance with approved designs and meets or exceeds the minimum design requirements under all applicable federal, state and local regulations; and that inspections are made by myself and include any appearances of instability, structural weakness or other hazardous condition of the structure affecting stability.

Signature:

CERTIFIED REPORT

IMPOUNDMENT EVALUATION

If you answer NO to these questions, please explain under comments

1. Is impoundment designed and constructed in accordance with the approved plan?

2. Is impoundment free of instability, structural weakness, or any other hazardous conditions?

3. Has the impoundment met all applicable performance standards and effluent limitations

from the previous date of inspection?

YES

COMMENTS/ OTHER INFORMATION

None

CERTIFICATION STATEMENT:

I hereby certify that: I am experienced in the construction of impoundments; I am qualified and authorized in the State of Utah to inspect and certify the condition and appearance of impoundments in accordance with the certified and approved designs for this structure; that the impoundment has been maintained in accordance with approved designs and meets or exceeds the minimum design requirements under all applicable federal, state and local regulations; and that inspections and inspection reports are made by myself or under my direction and include any appearances of instability, structural weakness or other hazardous conditions of the structure affecting stability in accordance with the Utah R645 Coal Mining Rules.

S. Scott Carlson, PE, Twin Peaks, P.C. By:

P.E. Number & State: 187727 UTAH

GENERAL INFORMATION

Coarse Refuse Pile

Report Date

January 14, 2013

Permit Number

C/007/035

Mine Name

Sunnyside Refuse and Slurry

Company Name

Sunnyside Cogeneration Associates

EXCESS SPOIL PILE OR REFUSE PILE IDENTIFICATION

Pile Name

Coarse Refuse Pile

Pile Number

N/A

MSHA ID Number 1211-UT-09-02093-01

Inspection Date

December 17, 2012

Inspected by

Rusty Netz

Reason for Inspection

Fourth Quarter Inspection 2012

Attachment to Report? (such as refuse sample analysis or photos)

NO

Field Evaluation

1. Foundation preparation, including the removal of all organic material and topsoil.

N/A

2. Placement of underdrains and protective filter systems.

N/A

3. Installation of final surface drainage systems

N/A

4. Placement and compaction of fill materials

N/A - Activities occurring at this time are associated with removal of refuse material

5. Final grading and revegetation of fill.

N/A

6. Appearances of instability, structural weakness, and other hazardous conditions

No aspects of the Fill structure were observed that could affect its stability or functionality

Coarse Refuse Pile

7. Other comments. Describe any changes in the geometry of the Excess Spoil/Refuse Pile structure, instrumentation, average and maximum lifts of materials placed in the pile, elevations of active benches, total and remaining storage capacity of the structure, evidence of fires in the pile and abatement of such fires, volumes of materials placed in the structure during the year, and any other aspect of the structure affecting its stability or function which has occurred during the reporting period

Refuse material is actively being excavated and removed from various locations across the top of the pile

QUALIFICATION STATEMENT:

I hereby certify that; I am experienced in the construction of earth and rock fills; I am qualified and authorized under the direction of a Registered Professional Engineer to inspect the condition and appearance of earth and rock fills in accordance with the certified and approved designs for this structure; that the fill structure has been maintained in accordance with approved design and meets or exceeds the minimum design requirements under all applicable federal, state and local regulations; and that inspections are made by myself and include any appearances of instability, structural weakness or other hazardous condition of the structure affecting stability.

CERTIFICATION STATEMENT

I hereby certify that: I am experienced in the construction of earth and rock fills; I am qualified and authorized in the State of Utah to inspect and certify the condition and appearance of earth and rock fills in accordance with the certified and approved designs for this structure; that the fill structure has been maintained in accordance with the approved design and meets or exceeds the minimum design requirements under all applicable federal, state, and local regulations; and, that inspections and inspection reports are made by myself or under my direction and include any appearances of instability, structural weakness or other hazardous conditions of the structure affecting stability.

By: S. Scott Carlson, PE, Twin Peaks, P.C.

P.E. Number & State: <u>187727 UTAH</u>

GENERAL INFORMATION

Excess Spoil Disposal Area #1

Report Date

January 14, 2013

Permit Number

C/007/035

Mine Name

Sunnyside Refuse and Slurry

Company Name

Sunnyside Cogeneration Associates

EXCESS SPOIL PILE OR REFUSE PILE IDENTIFICATION

Pile Name

Excess Spoil Disposal Area #1

Pile Number

N/A

MSHA ID Number <u>1211-UT-09-02093-04</u>

Inspection Date

December 17, 2012

Inspected by

Rusty Netz

Reason for Inspection

Fourth Quarter Inspection 2012

Attachment to Report? (such as refuse sample analysis or photos)

YES

Field Evaluation

1. Foundation preparation, including the removal of all organic material and topsoil.

N/A

2. Placement of underdrains and protective filter systems.

N/A

3. Installation of final surface drainage systems

N/A

4. Placement and compaction of fill materials

Approximately 24,605 tons of material were placed during the quarter.

5. Final grading and revegetation of fill.

N/A

6. Appearances of instability, structural weakness, and other hazardous conditions

Some smokers have been visible during previous quarters. None visible at this inspection.

Excess Spoil Disposal Area #1

7. Other comments. Describe any changes in the geometry of the Excess Spoil/Refuse Pile structure, instrumentation, average and maximum lifts of materials placed in the pile, elevations of active benches, total and remaining storage capacity of the structure, evidence of fires in the pile and abatement of such fires, volumes of materials placed in the structure during the year, and any other aspect of the structure affecting its stability or function which has occurred during the reporting period

Construction of the fill has been proceeding in shallow lifts in general conformance with the approved plan.

In accordance with the approved plan, SCA has gathered samples of the material placed in this Disposal Area through the year. The samples were composited in December and analyzed at the BYU Environmental Laboratory. Results from the analysis are attached.

QUALIFICATION STATEMENT:

I hereby certify that; I am experienced in the construction of earth and rock fills; I am qualified and authorized under the direction of a Registered Professional Engineer to inspect the condition and appearance of earth and rock fills in accordance with the certified and approved designs for this structure; that the fill structure has been maintained in accordance with approved design and meets or exceeds the minimum design requirements under all applicable federal, state and local regulations; and that inspections are made by myself and include any appearances of instability, structural weakness or other hazardous condition of the structure affecting stability.

CERTIFICATION STATEMENT

I hereby certify that: I am experienced in the construction of earth and rock fills; I am qualified and authorized in the State of Utah to inspect and certify the condition and appearance of earth and rock fills in accordance with the certified and approved designs for this structure; that the fill structure has been maintained in accordance with the approved design and meets or exceeds the minimum design requirements under all applicable federal, state, and local regulations; and, that inspections and inspection reports are made by myself or under my direction and include any appearances of instability, structural weakness or other hazardous conditions of the structure affecting stability.

By: S. Scott Carlson, PE, Twin Peaks, P.C. P.E. Number & State: 187727 UTAH

BRIGHAM YOUNG UNIVERSITY

Environmental Analytical Laboratory 244 WIDB Provo, UT 84602 801-422-2147

Plant and Wildlife Sciences Department

S 0 1

Name	SCA		SAMPLE IEST REPURT	Date:	12-Dec-12
Street	#1 Power Plant R	oad	AND	Telephone:	435-888-4476
Sunnysid	e Utah	84526	RECOMMENDATIONS	Fax:	
City	State	Zip			

Sample Identification	Crop to be grown	рН	% Sand	% Silt	% Clay	Soil Texture	% Moisture	% Organic Carbon
#1 Spoils sample	Turf	7.1	61.7	24.2	14.1	Sandy Loam	42.3	5.1

Test	Results	Very Low	Low	Medium	High	Very High	Recommendations
Nitrate-Nitrogen ppm N	3	х					
Phosphorus ppm P	1	х	:				
Potassium ppm K	84			х			
Salinity-ECe dS/m	3.0			х			no salinity problem
Boron ppm B	2.1						
Selenium ppm Se	0.47						
SAR-Sodium Absorption Ratio	0.74	х				:	no sodium hazard
Calcium-SAR ppm Ca	885						
Potassium SAR ppm K	31						
Magnesium SAR ppm Mg	304						
Sodium SAR ppm Na	101						
Sulfur % pyritic S	0.4						
Acid Potential tons CaCO3/1000 tons	11.1						
Ca Carbonate %CaCO3	4.2						
Neutralization Pot. tons CaCO3/1000 tons	42.2						
Acid Base Potential tons CaCO3/1000 tons	31.2						

Notes:

GENERAL INFORMATION

Excess Spoil Disposal Area #2

Report Date

January 14, 2013

Permit Number

C/007/035

Mine Name

Sunnyside Refuse and Slurry

Company Name

Sunnyside Cogeneration Associates

EXCESS SPOIL PILE OR REFUSE PILE IDENTIFICATION

Pile Name

Excess Spoil Disposal Area #2

Pile Number

N/A

MSHA ID Number

1211-UT-09-02093-05

Inspection Date

December 17, 2012

Inspected by

Rusty Netz

Reason for Inspection

Fourth Quarter Inspection 2012

Attachment to Report? (such as refuse sample analysis or photos)

NO

Field Evaluation

1. Foundation preparation, including the removal of all organic material and topsoil.

Site preparation on XS2 Phase 2 area has been completed by excavating subsoil and placing on Phase 1 for reclamation. Phase 3 area is not yet prepared for material placement.

2. Placement of underdrains and protective filter systems.

No under-drains or filters are required by the approved plan for phase 1 or phase 3. One permanent culvert is to be installed at some point prior to completing fill on the Phase 2 area. Ample capacity exists for initial fill placement prior to reaching the location requiring the culvert.

3. Installation of final surface drainage systems

Phase 1 portion has been surface roughened to control drainage.

4. Placement and compaction of fill materials

No new spoils or coal reject material was placed in this disposal area during the quarter.

5. Final grading and revegetation of fill.

Phase 1 portion has been covered with 4ft, mulch & fertilizer incorporated and reseeded. Vegetation is proceeding slowly due to lack of rain. SCA conducted additional seeding during the 4th quarter 2012 to assist with revegetation.

6. Appearances of instability, structural weakness, and other hazardous conditions

No aspects of the Fill structure were observed that could affect its stability or functionality

Excess Spoil Disposal Area #2

7. Other comments. Describe any changes in the geometry of the Excess Spoil/Refuse Pile structure, instrumentation, average and maximum lifts of materials placed in the pile, elevations of active benches, total and remaining storage capacity of the structure, evidence of fires in the pile and abatement of such fires, volumes of materials placed in the structure during the year, and any other aspect of the structure affecting its stability or function which has occurred during the reporting period

SCA has completed reclamation work on Phase 1 of this Disposal Area. Subsoil materials were excavated from the proposed Phase 2 area to provide approximately 3 ft of cover over the spoil materials. Salvaged Topsoil and clean borrow material was placed to provide the top (4th) foot of cover. Weed free straw mulch and fertilizer was incorporated as described in the permit. Reseeding occurred in accordance with the approved mix.

SCA received approval on a permit amendment for expansion of this Disposal Area into Phase 2 and 3 areas. The Phase 2 area has been prepared for fill placement. Phase 3 is not expected to be prepared for several years to come.

OUALIFICATION STATEMENT:

I hereby certify that; I am experienced in the construction of earth and rock fills; I am qualified and authorized under the direction of a Registered Professional Engineer to inspect the condition and appearance of earth and rock fills in accordance with the certified and approved designs for this structure; that the fill structure has been maintained in accordance with approved design and meets or exceeds the minimum design requirements under all applicable federal, state and local regulations; and that inspections are made by myself and include any appearances of instability, structural weakness or other hazardous condition of the structure affecting stability.

CERTIFICATION STATEMENT

I hereby certify that: I am experienced in the construction of earth and rock fills; I am qualified and authorized in the State of Utah to inspect and certify the condition and appearance of earth and rock fills in accordance with the certified and approved designs for this structure; that the fill structure has been maintained in accordance with the approved design and meets or exceeds the minimum design requirements under all applicable federal, state, and local regulations; and, that inspections and inspection reports are made by myself or under my direction and include any appearances of instability, structural weakness or other hazardous conditions of the structure affecting stability.

By: S. Scott Carlson, PE, Twin Peaks, P.C.

P.E. Number & State: 187727 UTAH